

Ulti-Line Universal Tile Vent

Description

The Universal Vent Tiles has been designed so that it can fit with any single or double lap roof tile. When being used with Metric Tile Profiles it can be fitted without Tile Cuts. If using a larger or smaller format Tile cutting maybe required. It is available in up to five caps colours with a maximum airflow of 20,000 mm² airflow and can be laid down to 12½° roof pitch. If used for Roof Ventilation for 20,000 mm² space every 2 m for 5,000 mm² space every 4m.

Guidelines for use

Fitted whilst laying the roof (can be retro fitted as well). Roof membrane needs to be cut to allow penetration into roof space, with membrane folded back over top batten. Can be used on any interlocking or double lap tile. Can be used in conjunction with Flexi-Pipe ULTI3FP if connection required and can be adapted for DN125 or DN150.

Specifications	
Product code	ULTI3UVT
Free airflow	Maximum of up to 20,000 mm ²
Units of measure	1 PC/Carton
Weight	1390 g
Material	Flexible and rigid PVC, ASA, butylon and metalwork
Manufacturing process	Injection moulding and assembly
Colours	Black, Grey, Brown, Red, Terracotta



All products are covered by our 15 year Durability Warranty terms and conditions can be found on our website.



All plastic products are made in UK.



ulti-mate-roofing.co.uk

For more information contact us: 0345 565 3101 | sales@ulti-mate-roofing.co.uk

Ulti-Mate Roofing & Building Products | Bee Mill, Shaw Road, Royton, Oldham, OL2 6EH